

Charging Station Solution

PV & ESS & EV Charging Solution

- ☐
- ☐
- ☐
- ☐
- ☐
- ☐


- ☐
- ☐
- ☐

SHENZHEN MEGMEET ELECTRICAL CO., LTD.

FOLLOW US







Contents

01-14	Charger
15-28	Charging Module
29-31	Charger Components
32	R&D Capability
33-34	Manufacturing Capacity

Super Fast Charging Stations

SFC 30



Universal compatibility



Smart connectivity



Safe & reliable



Efficient & convenient

AC Input	
	≥
DC Output	
	≥
	≥
	≥
	≥
Working Environment Conditions	
	≥
Function	
Appearance	

Super Fast Charging Stations

SFC 40



AC Input

	> >

DC Output

	≡
	≡ > ≡
	≡

Working Environment Conditions

	≡

Function

Appearance

Super Fast Charging Stations


SFC 60



AC Input	
	≧
DC Output	
	≧
	≧
	≧
	<
Working Environment Conditions	
	≧
Function	
Appearance	

Super Fast Charging Stations

SFC 60 to 180



Fast charging



Safe & efficient



Intelligent operation & Maintenance



Flexible expansion

AC Input	
	> >
DC Output	
	≡
	≡
	≡
	≡
Working Environment Conditions	
	≡
Function	
Appearance	

Super Fast Charging Stations

SFC 150



Fast charging



Safe & efficient



High-grade protection



Flexible efficient

AC Input

≧

DC Output

≧

≧

≧

≧

Working Environment Conditions

≧

Function

Appearance



AC Input	
	≥
DC Output	
	≈
	≈
	≥
	≈
Working Environment Conditions	
	≈
Function	
Appearance	




Split Type Super Fast Charging Stations

Liquid cooling supercharging

Flexible allocation

Intelligent operation & maintenance

Safe & efficient



20 kW Charging Module



Wide constant power range




State grid unified size



Flexible expansion



Intelligent control



AC Input

<

>

>

<

DC Output

≡

≡

≡

≡

≡

Monitor

Working Environment Conditions

≡

>

Product Reliability and Safety

Alarm and Protection

Dimensions and Weight

20 kW Charging Module



Low voltage and high current




High power density



Flexible expansion



Intelligent control



AC Input	
	<
	> >
	<
DC Output	
	≡
	≡
	≡
	≡
Monitor	
Working Environment Conditions	
	≡ >
Product Reliability and Safety	
	>
Alarm and Protection	
Dimensions and Weight	

20 kW Charging Module



Low voltage and high current




High power density



Flexible expansion



Intelligent control



AC Input

<

>

>

<

DC Output

≈

≈

≈

≈

≈

Monitor

Working Environment Conditions

≈


>

Product Reliability and Safety


>

Alarm and Protection

Dimensions and Weight



60 kW Charging Module



AC Input

<

≧

DC Output

≧

≧

≧

≧

≧

Monitor

Working Environment Conditions

≧

Product Reliability and Safety

>

Alarm and Protection


Dimensions and Weight

25 kW Charging Module



DC Input	
	<
DC Output	
	>
Monitor	
Working Environment Conditions	
Product Reliability and Safety	
Alarm and Protection	
Dimensions and Weight	

Charger Communication Control Unit (CCU)



Input voltage:

—

Interface parameters:


—

—

—

—

Charger Telematics Control Unit (TCU)



Input voltage:

—

Storage chip:

—

—


Interface parameters:

—


—

—

Charger Protocol Converter (PLC)



R&D CAPABILITY



- -
 -
 -
 -
 -
- -
 -
 -
 -
 -

Charging standards:	—	Communication port:	—
Electricity supply:	—	Dimension:	—
	—		
Working power consumption:	— <	Range of working temperature:	—





ODM

PEM

